


- Hose** : COOLING WATER HOSE
- Application** : Hoses are to be used for suction & delivery applications in engine coolant system on yachts and small craft.
Hoses can also be used for marine wet exhaust systems on yachts and small craft.
- Features** : Suitable for suction and pressure
Suitable for salt and fresh water
Suitable for all cooling fluids
Exhaust gases and fuel residues resistant
- Lining** : Black EPDM rubber
- Reinforcement** : Woven synthetic fabric and steel helix wire embedded between the layers.
- Cover** : Heat and ozone resistant, BLACK, corrugated, EPDM rubber.
- Temperature** : Suitable for use in the range - 30 to + 120° Celsius
- Relevant CE Standards** : Non
- Classification** : Non

Code	I.D.		O.D	Steel Wire		Working Pressure		Burst Pressure		Bending Radius		Force		Weight	
				Diam.	Pitch										
	mm	inch	mm	mm	mm	bar	psi	bar	psi	mm	inch	N	kg/m	lbs/ft	
MWHOSE19	19	3/4	28	1.0	10	2.5	37.5	10	145	29	1 1/8	2.0	0.39	0.26	
MWHOSE25	25	1	34	1.0	9	2.5	37.5	10	145	38	1 1/2	3.0	0.51	0.34	
MWHOSE32	32	1 1/4	41	1.0	8	2.5	37.5	10	145	48	1 7/8	3.5	0.71	0.48	
MWHOSE38	38	1 1/2	47	1.5	9	2.5	37.5	10	145	57	2 1/4	3.5	0.88	0.59	
MWHOSE51	51	2	60	1.5	9	2.5	37.5	10	145	77	3 1/16	4.0	1.15	0.77	

Identification:

 MARINE WATER HOSE - I.D. 25 mm
<p>Green ribbon over full length of hose 0.5 meter Mark, Hose type and dimension repeated every 0.5 meter</p>