

DULON POLY POLISH RUBBING COMPOUND STRONG 14



STRONG POLISH

DESCRIPTION

Professional polishing paste with a strong granular formula. It restores heavily weathered, chalky, stained and dull surfaces and it removes fine scratches and persistent stains and streaks. It can be used on hard surfaces like gel coat, painted steel and wood, stainless steel. After application, protect the surface with DULON 1&2 or DULON PREMIUM BOAT WAX 19.

- Restores weathered, chalky, stained and dull surfaces to new.
- Removes fine scratches and persistent stains and streaks.
- Easy to apply & economical in use.
- Can be used both manually or by machine.

INSTRUCTIONS

PRETREATMENT (if required)

- Use DULON HULL & WATERLINE CLEAN 22 to remove scale and brownish/yellow stains.
- Use PREDULON 00 to remove surface dirt, grease, oil, old wax and silicon traces.

POLISHING - MANUALLY

1. Apply DULON POLY POLISH with a damp microfibre cloth, polish pad or sponge by circular motions, until the desired result is achieved.
2. Remove polish residue by using a dry microfibre cloth.

POLISHING - MACHINE (concentric + hard polishing pad)

1. Lightly moisten the polishing pad (hard) and apply a small amount on the pad.
2. Spread DULON POLY POLISH thinly over surface.
3. Polish the surface at low speed, in gentle, controlled movements - horizontally and vertically.
4. Increase rotation speed slightly during polishing process until desired result is achieved.
5. Remove the polish residue using a microfibre cloth.

After treatment, protect the polished surface with the DULON 1 & 2 or DULON PREMIUM BOAT WAX 19.

AVAILABLE PACKAGING

Article number	Product	Packaging	Content
6-14005	Dulon Polish Rubbing Compound Strong 14	Bottle	500ml
6-14050	Dulon Polish Rubbing Compound Strong 14	Can	5L
6-14250	Dulon Polish Rubbing Compound Strong 14	Can	25L

TIPS & TRICKS

- Use a concentric polishing machine with a hard polishing pad.
- Also suitable to use on your car, caravan or camper.



DULON POLY POLISH RUBBING COMPOUND STRONG 14



STRONG POLISH

C.R.P. INDICATOR

- Clean.
- Restore.

STORAGE & USE

- DULON POLY POLISH RUBBING COMPOUND (500 ml) will treat 10-15 meter vessel.
- Store frost-free, in a dark and dry place.
- Ideal working temperature between de 5 en 25 °C.
- Do not use in direct sun light.

YOU MAY ALSO LIKE

- Dulon Poly Polish Rubbing Compound Medium 15.
- Dulon Poly Polish Rubbing Compound Fine 16.

RELATED PRODUCTS

- Predulon 00.
- Dulon 1&2
- Dulon Premium Boat Wax 19.
- Dulon Hull & Waterline Clean 22.

