DULON PREMIUM BOAT WAX 19

PROFESSIONAL BOAT WAX



DESCRIPTION

First class quality protection product with PTFE elements, special developed for new boats or boats in superb condition. PREMIUM BOAT WAX 19 is easy to apply and provides a high gloss finish. Optimum protection during the whole sailing season.

- First class boat wax with PTFE elements.
- Extreme shine & protection throughout the sailing season.
- Easy-On-Easy-Off

INSTRUCTIONS

PRETREATMENT (if required)

- Use DULON HULL & WATERLINE CLEAN 22 to remove scale and brownish/yellow stains.
- Use DULON POLY POLISH RUBBING COMPOUND (strong, medium or fine) to restore weathered surfaces also to remove dull patches, scratches, persistent stains and streaks.
- Use PREDULON 00 to remove surface dirt, grease, oil, old wax and silicon traces.

POLISHING - MANUALLY

- 1. Apply DULON PREMIUM BOAT WAX 19 with a damp microfibre cloth, polish pad or sponge by circular motions, until the desired result is achieved.
- 2. Let it dry and rub / buff with a clean, dry microfibre cloth or lambswool pad.

POLISHING - MACHINE (concentric + soft polishing pad and lambswool pad)

- 1. Lightly moisten the polishing pad (soft) and apply a small amount on the pad.
- 2. Spread DULON PREMIUM BOAT WAX 19 thinly on the surface.
- 3. Polish the surface at low speed, in gentle, controlled movements horizontally and vertically.
- 4. Increase rotation speed slightly during polishing process until desired result is achieved.
- 5. Buff / rub with a clean, dry lambswool pad at high rotation speed.

AVAILABLE PACKAGING

Article number	Product	Packaging	Content
6-19005	Dulon Premium Boat Wax 19	Bottle	500ml
6-19050	Dulon Premium Boat Wax 19	Can	5L
6-19250	Dulon Premium Boat Wax 19	Can	25L

TIPS & TRICKS

- Use a concentric polishing machine with a soft polishing pad and lambswool pad.
- Also suitable to use on your car, caravan or camper.
- Wash the treated surface at regular intervals using DULON PREMIUM SHAMPOO 03 –
 WASH & WAX. It has special additives which maintains and extends the protective effect.

C.R.P. INDICATOR

Protect



DULON PREMIUM BOAT WAX 19

PROFESSIONAL BOAT WAX



STORAGE & USE

- DULON PREMIUM BOAT WAX 19 (500 ml) will treat 10-15 meter vessel.
- Store frost-free, in a dark and dry place.
- Ideal working temperature between de 5 en 25 °C.
- Do not use in direct sun light.

YOU MAY ALSO LIKE

- Dulon 1&2
- Dulon Polish & Wax Compound 18.
- Dulon Premium Boat Wax 19.

RELATED PRODUCTS

- Predulon 00.
- Dulon Premium Shampoo 03.
- Dulon Poly Polish Rubbing Compound Strong 14 / Medium 15 / Fine 16.
- Dulon Hull & Waterline Clean 22.

