

DULON TEAK PROTECTOR

TEAK PROTECTOR WITH UV-BLOCKER



DESCRIPTION

Phase 3 of the 3-STEP TEAK CARE SYSTEM

A revolutionary protection product with UV-blocker used on teak (decks) or furniture. It slows down the process of colouring/greying, prevents lime scale and algal growth. It provides protection during the whole sailing season. It creates a water- and dirt proof coating and does not become greasy or slippery.

- Protects teak during the sailing season.
- Delays greying due to UV blocker.
- Creates invisible water and dirt repellent layer.
- Prevents limescale and / or algae growth.
- Does not get slippery or slippery.

INSTRUCTIONS

PRETREATMENT (if required)

- Use DULON TEAK DEGREASER 41 to remove stains of (winch)grease, (suntan) oils, diesel- and fuel spatters, etc.
- Use DULON TEAK CLEAN & BRIGHTENER 42 to restore weathering, greying, algae growth and to remove lime scale, green fur etc.

PROTECTING

Surface should be clean and oil- and grease free.

— SHAKE BEFORE USE —

1. Apply DULON TEAK PROTECTOR 43 pure, steady and frugal on to the surface using a flat brush or paint roller.
2. Avoid sheets and drops, remove extensive fluid using cloth or paper.
3. Drying time aprox. 20-30 minutes.

DULON TEAK PROTECTOR 43 will be complete impregnated and activated after at least 24 hours (during this period do not charge with oil or water).

AVAILABLE PACKAGING

Article number	Product	Packaging	Content
6-43005	Dulon Teak Protector 43	Flacon	500ML
6-43050	Dulon Teak Protector 43	Can	5L
6-43250	Dulon Teak Protector	Can	25L

TIPS & TRICKS

- Also ideal to treat wooden garden furniture.



DULON TEAK PROTECTOR

TEAK PROTECTOR WITH UV-BLOCKER



C.R.P. INDICATOR

- Protect.

STORAGE & USE

- DULON TEAK PROTECTOR 43 (500 ml) treats a maximum of 10m².
- Store frost-free, in a dark and dry place .
- Apply above 0°C.
- do not use in direct sun light.

YOU MAY ALSO LIKE

-

RELATED PRODUCTS

- Dulon Teak Degreaser 41.
- Dulon Teak Clean & Brightener 42.

IMPORTANT INFORMATION

Inhalation of aerosol and / or nebulized product may cause respiratory irritation. It is important to take the necessary measures to avoid exposure to the atomized product.

HAZARD + PRECAUTIONARY STATEMENTS



GHS03-08-09 DANGER

H226: Flammable liquid and vapour. H304: May be fatal if swallowed and enters airways H411: Toxic to aquatic life with long-lasting effects EUH066: Repeated exposure may cause skin dryness or cracking

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking. P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical/ventilating/lighting/equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P280 - Wear protective gloves/protective clothing/eye protection/face protection. P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. P303 + P361 + P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. P331 Do NOT induce vomiting. P332 + P313 If skin irritation occurs: Get medical advice/attention. P370 + P378 In case of fire: Use for extinction. P403 + P235 Store in a well-ventilated place. Keep cool. P405 Store locked up. P501 Dispose of contents/container to local regulations.

