Gelomat

Le Tonkinois Gelomat Matting Agent -
Add to the last coat to obtain a satin to matte finish.

Product description

Application area	Gelomat is added to all Le Tonkinois paints to give the paint a matte or satin sheen. Gelomat is homogenized by simply mixing it with the paint before applying the coating color.

Processing

Processing	You can achieve different levels of mattness, ranging from matte, to silk matte to silk gloss. You will obtain a uniform effect if you always mix paint or varnish with the same quantity of Gelomat, taking into account the proportions mentioned below:
	Matt: mix Gelomat and varnish in equal amounts.
	Silk matt: mix 1/3 Gelomat with 2/3 varnish.
	Silk gloss: Gelomat and varnish in a ratio of one to three.
	Ensure good ventilation during application.
Usage	Depending on the desired matting, see mixing ratio.
Drying time	According to the product to be matted.

Substrates and their pretreatment

Underground	see product to be matted

Product information

Ingredients	Isoaliphate
VOC Safety Notice	see product to be matted
Storage	Store tightly closed and out of reach of children. Store in a cool but frost-free place.
Shelf life	Unopened Shelf life almost unlimited.
Disposal	Do not dispose of paint or solvent residues in waste water or soil, or during processing! Completely dried residues of this product can be disposed of with household or residual waste; empty cans (tinplate) belong in the respective local recycling containers or yellow bags/bins (Green Dot).
Safety instructions	For safety-relevant information, please refer to the corresponding safety data sheet.

Since 1906:
Ets. Joubert & Cie F - Ivry-sur-Seine

Palm Norge GmbH, Feldlinie 32,
26160 Bad Zwischenahn

info@barendpalm.de

To achieve optimum results, please observe the technical data sheets of all products used.
The information is based on our current knowledge and experience. However, they do not constitute a guarantee of product properties and do not establish a contractual legal relationship. With the publication of this Technical Data Sheet, all previous information becomes invalid.