



Wachslasur

Glazing, water vapor permeable, easy to apply water-based glaze.
Fast drying and polishable.



Product description

Application area	For colored design of wooden ceilings and wall coverings as well as wooden furniture parts in the interior.
Color shade	Shades are intermixable or can be stretched with the wax glaze colorless.

Processing

Processing	Stir / shake well before use. Depending on the desired coverage, apply the wax glaze evenly 1 - 2 times. A silky glossy finish is achieved by polishing the surface with a polishing brush or a lint-free cloth under light pressure. cloth under light pressure. The glaze may stain slightly in the beginning. For finishing, we recommend a final coat of wax glaze colorless.
Usage	Approx. 60 - 100 ml/m ² or 10 - 17 m ² /l depending on the absorbency of the wood.
Drying time	After 25 to 30 minutes, a 2nd coat can be applied. After 45 minutes, the surface can be polished. Dried through after approx. 24 hours.

Substrates and their pretreatment

Underground	The substrate must be dry, solid, clean, grease and dust-free. Wood surfaces Depending on the type of wood and desired penetration depth, pre-sand with 100 - 180 grit in the direction of the grain. Application: Apply with brush, sponge or cotton cloth. Room and surface temperature above 15°C.
--------------------	--

Product information

Ingredients	Water, carnauba wax, micro wax, methyl cellulose.
VOC Safety Notice	The VOC content of this product is max. 1 g/l. The EU limit is 30 g/l (category "a" as of 2010).
Storage	Store in a cool, dry and closed place. Protect from frost!
Shelf life	Original sealed stable for about 4 years.
Disposal	In accordance with local, official regulations. Dried product residues can be disposed of with household waste. Waste code: EAK 08 01 20
Safety instructions	Contains 1,2-benzisothiazol-3(2H)-one. May cause allergic reactions. Safety data sheet available on request. Keep out of the reach of children. Avoid release to the environment. Dispose of contents / container to proper recycling.

To achieve optimum results, please observe the technical data sheets of all products used.
The information is based on our current knowledge and experience. However, they do not constitute a guarantee of product properties and do not
establish a contractual legal relationship. With the publication of this Technical Data Sheet, all previous information becomes invalid.



Since 1906:
Ets. Joubert & Cie F - Ivry-sur-Seine



Palm Norge GmbH, Feldlinie 32,
26160 Bad Zwischenahn



info@barendpalm.de