



## Wetterschutzöl

The weather- and UV-resistant coating for refreshing old coatings or as a new coating on untreated wood outdoors. Used especially on glazes and wood preservatives, it protects them from graying due to UV and weather influences. A silk-matt, hard-wearing, dirt- and water-repellent surface is achieved. The natural oils refresh old coatings and penetrate deeply into the new wood. Permanently flexible, the weather protection oil thus reduces swelling and shrinkage of the wood. The coating does not crack and does not flake off.



## Product description

### Application area

For the treatment of all types of wood. For wooden facades, playground equipment, shutters, fences, pergolas, wooden shingles, garden furniture and summer houses, carports, etc.

## Processing

### Processing

Stir / shake container well before use. The optimum processing temperature is above 15°C. Do not apply under direct sunlight. The substrate must be dry, clean, free of resin and dust. If necessary, carry out a fine final sanding with grit 100 - 120. Loose paint and varnish coats must be completely removed. Apply thinly and evenly with a brush or flat brush. Allow to dry. Repeat application 1 - 2 times. In case of renovation, one coat is usually sufficient to refresh the cleaned surface without sanding!

### Usage

The application quantity must be determined by trial application at the beginning of processing. Empirical values depending on absorbency and final sanding of the wood: 50 - 70 ml/m<sup>2</sup> Yield: 15 - 20 m<sup>2</sup>/l.

### Drying time

#### In normal climate:

At 20°C and 50% relative humidity: Dust dry after approx. 12 hours.  
Dry and recoatable after 24 hours.

### Cleaning the tools

With Le Tonkinois Verdünnung.

# TECHNICAL DATA SHEET

Wetterschutzöl

**LE TONKINOIS**

## Substrates and their pretreatment

**Underground** The substrate must be dry, solid, clean, grease and dust-free. Brush out rough sawn wood beforehand.

## Product information

**Ingredients** Wood oil boiling, linseed oil, natural resin esters, isoparaffins, kaolin, wax, zinc oxide, mineral pigments as UV protection

**VOC Safety Notice** The VOC content of this product is max. 420 g/l. EU limit max. 700 g/l.

**Storage** Store in a cool, dry and closed place.

**Shelf life** Original sealed stable for at least 5 years.

**Disposal** In accordance with local, official regulations. Dried up product residues can be disposed of with household waste. Waste code: 08 01 11

**Safety instructions** For safety-relevant information, please refer to the corresponding safety data sheet.

Natural paints have a characteristic odor due to the vegetable oils used. Ensure good ventilation during processing. Drying oils can ignite spontaneously. Therefore, do not crumple up rags contaminated with this product, but let them dry spread out or soak them in water before disposing of them.

To achieve optimum results, please observe the technical data sheets of all products used.  
The information is based on our current knowledge and experience. However, they do not constitute a guarantee of product properties and do not establish a contractual legal relationship. With the publication of this Technical Data Sheet, all previous information becomes invalid.



Since 1906:  
Ets. Joubert & Cie F - Ivry-sur-Seine



Palm Norge GmbH, Feldlinie 32,  
26160 Bad Zwischenahn



info@barendpalm.de